

### HDMS-1044K

Order No. 06.9370



**HDMI™ quad splitter**, for alternatively connecting 1 player to up to 4 HDMI™ monitors.

- For transmission of high-definition UHD signals (4K)
- Supports HDR
- Compact, space-saving version
- Input: 1 x 19-pole HDMI™ Type-A jack

- Outputs: 4 x 19-pole HDMI™ Type-A jack
- Power is provided via encl. power supply
- Dimensions: 139 x 22 x 64 mm
- Weight: 225 g



### HDMS-2084K

Order No. 06.9380



**8-way HDMI™ splitter**, for alternatively connecting 2 players to up to 8 HDMI monitors.

- For transmission of high-definition UHD signals (4K)
- Supports HDR
- Input source can be selected via switch and via enclosed infrared remote control

- Inputs: 2 x 19-pole HDMI™ Type-A jack
- Outputs: 8 x 19-pole HDMI™ Type-A jack
- Power is provided via encl. power supply
- Dimensions: 276 x 25 x 140 mm
- Weight: 877 g



### HDMS-3014K

Order No. 06.9390



**3-way HDMI™ switcher**, for connecting 3 players to 1 HDMI™ monitor.

- For transmission of high-definition UHD signals (4K)
- Supports HDR
- Input source can be selected via switch or supplied infrared remote control

- Inputs: 3 x 19-pole HDMI™ jack
- Output: 1 x 19-pole HDMI™ jack
- Power is provided via encl. power supply
- Dimensions: 111 x 21 x 53 mm
- Weight: 154 g



### HDMS-5014K

Order No. 06.9400



**5-way HDMI™ switcher**, for connecting 5 players to 1 HDMI™ monitor.

- For transmission of high-definition UHD signals (4K)
- Supports HDR
- Compact, space-saving version
- Input source can be selected via switch or supplied infrared remote control

- Inputs: 5 x 19-pole HDMI™ Type-A jack
- Output: 1 x 19-pole HDMI™ Type-A jack
- Power is provided via encl. power supply
- Dimensions: 159 x 22 x 64 mm
- Weight: 246 g



### HDMQS-1044K

Order No. 06.9350



**HDMI™ quad splitter**, for connecting 4 players to 1 HDMI™ monitor.

- Input source and display mode can be selected via supplied infrared remote control

- Inputs: 4 x 19-pole HDMI™ Type-A jack
- Outputs: 1 x 19-pole HDMI™ Type-A jack, 1 x coaxial
- Power is provided via encl. power supply
- Dimensions: 220 x 23 x 87 mm



### HDMR-1014K

Order No. 06.9360



**HDMI™ repeater**, for connecting 2 HDMI™ cables and for signal amplification. For cable lengths of up to 30 m (1080p) or 20 m (4K) without signal loss.

- For transmission of high-definition UHD signals (4K)
- Supports HDR

- 2 x 19-pole HDMI™ jack
- Power (= 5 V/300 mA) is provided via optional power supply PSS-1005USB. Supplied with suitable USB connection cable
- Dimensions: 49 x 16 x 31 mm



### HDRCA-100CON

Order No. 18.3960



**HDMI™/composite converter**, for converting a digital HDMI™ signal into an analogue component AV signal.

- Input: 1 x 19-pole HDMI™ jack
- Outputs: 3 x RCA (video, audio L, audio R)

- PAL/NTSC selector switch
- Metal housing with mounting flange
- Supplied with mounting accessories
- Admissible ambient temperature: 0-40 °C
- Power is provided via enclosed plug-in power supply

