

16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

ATS-22R

Order No. 0257110

16-channel miniature receiver, with intercom function.

- Intercom function with transmitter ATS-22T via push-button
- Built-in microphone
- Supplied with matching clip-on earphone

- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)

- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 87 x 12 mm

Licence-free in the EU.



ATS-22T

Order No. 0257120

16-channel miniature transmitter, for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R

- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 70 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)

- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.



ATS-20R

Order No. 0255640

16-channel miniature receiver

- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)

- LCD for indicating channel, carrier signal, volume and battery status
- Autolock function
- Lanyard
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option

- Dimensions: 40 x 87 x 12 mm
- Weight: 37 g

Licence-free in the EU.



ATS-20T

Order No. 0255650

16-channel miniature transmitter, for microphone operation and audio line signals.

- Supplied with electret tie clip microphone
- Microphone input/audio line input via 3.5 mm jack with automatic detection,

- depending on the configuration (mono/stereo)
- LCD for indicating channel and battery status
- Mute button
- Lanyard
- Transmitting power: ≤ 10 mW (EIRP), operating range: approx. 100 m

- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

Licence-free in the EU.



ATS-12CB

Order No. 0255660

Transport bag with integrated charging function, for transmitters and receivers of the ATS-20 series.

- For simultaneously charging rech. batteries of up to 12 devices
- Each slot with LED for indicating battery charging status

- Black nylon bag with zip fastener, carrying handle and compartments for accessories
- Supplied with matching power supply
- Dimensions: 350 x 110 x 120 mm
- Weight: 1.03 kg



ATS-35CB

Order No. 0255670

Transport bag with integrated charging function, for transmitters and receivers of the ATS-20 series.

- For simultaneously charging rech. batteries of up to 35 devices
- Each slot with LED for indicating battery charging status

- Black nylon bag with zip fastener, carrying handle and compartments for accessories
- Supplied with matching power supply
- Dimensions: 420 x 140 x 250 mm
- Weight: 2.9 kg

