

Speakers

Speaker Systems

MKS-248/SW

Order No. 0132040



MKS-248/WS

Order No. 0132050



Pairs of 2-way wall-mount design speaker systems, 60 W, 8 Ω

- High-performance PA speaker systems (bass-reflex) with a perfect sound
- Each equipped with 2 x 10 cm polypropylene bass-midrange speaker and 1 x high-quality dome tweeter
- High efficiency, high power capability
- White plastic housing with lacquered aluminium grille
- Supplied with matching metal wall bracket (for pivoting and tilting)

Model	MKS-248/SW	MKS-248/WS
Total power rating	100 W	100 W
Power rating (RMS)	60 W	60 W
Frequency range	70-20,000 Hz	70-20,000 Hz
Sensitivity	89 dB/W/m	89 dB/W/m
Dimensions	150 x 300 x 190 mm	150 x 300 x 190 mm
Weight	3.4 kg	3.4 kg



MKS-232/SW

Order No. 0132160



MKS-232/WS

Order No. 0132170



Pairs of weatherproof 2-way wall-mount speaker systems, 30 W, 8 Ω

- PA speaker systems with an excellent sound
- 13 cm polypropylene bass-midrange speaker and dome tweeter
- High efficiency
- Black (SW) or white (WS) plastic housing with lacquered aluminium grille
- Supplied with matching metal wall brackets

Model	MKS-232/SW	MKS-232/WS
Total power rating	50 W	50 W
Power rating (RMS)	30 W	30 W
Impedance	8 Ω	8 Ω
Sensitivity	89 dB/W/m	89 dB/W/m
Protection class	IP55	IP55
Admiss. ambient temp.	-20 °C to +50 °C	-20 °C to +50 °C
Dimensions	160 x 260 x 180 mm	160 x 260 x 180 mm
Weight	1.8 kg	1.8 kg



MKS-48/WS

Order No. 0132130



Pair of wall/ceiling/corner mount speaker systems, 15 W, 8 Ω

These really universally mountable speakers allow a perfect integration into most versatile indoor mounting positions. Interesting possibilities due to the optional creation of a cluster with 1-4 elements, from ceiling suspension in a corner to a hemisphere of wide radiation in the middle of the wall or ceiling. The sound of the pure white speakers is adjusted in such a precise way that it provides a complete sound of high quality, no matter in which position the speakers are placed.

- White ABS cabinet
- High-quality 10 cm full range speaker
- Variable support and mounting system

Model	MKS-48/WS
Total power rating	30 W
Power rating (RMS)	15 W
Frequency range	100-20,000 Hz
Sensitivity	87 dB/W/m
Dimensions	195 x 145 x 140 mm
Weight	1.5 kg

