

## SOUND-100SUB

Order No. 0250730



### Active subwoofer system, 120 W

- Active subwoofer for adding to the active SOUND speaker systems, but also to any other compact speaker for hi-fi or home cinema applications and home recordings
- The amplifier features a variable input sensitivity, a phase switch and an automatic switch-on system which can additionally be activated as well as an adjustable crossover frequency (50-150 Hz)
- High-quality bass-reflex MDF cabinet (black wood veneer look)
- 25 cm (10") bass speaker
- Volume control for the subwoofer
- Inputs via 1 x RCA L/R, RCA LFE or screw terminals for high-level L/R
- Additional outputs for mid-high range speakers, thus well-suited for connection to already existing speaker cables

Model	SOUND-100SUB
Power rating (RMS)	120 W
Frequency range	35-100 Hz
Input signal	150 mV/24 k $\Omega$ (RCA L/R) 55 mV/16 k $\Omega$ (RCA mono) 2.3 V/440 $\Omega$ (high IN)
Sensitivity	88 dB/W/m
Power supply	~ 230 V/50 Hz/240 VA
Dimensions	330 x 360 x 360 mm
Weight	13 kg
Inputs	1 x RCA (L/R), unbal., IN 1 x RCA (mono), unbal., IN 1 x screw terminal (stereo), high-level IN
Outputs	1 x screw terminals (stereo), high-level out

## ESUB-8F/WS

Order No. 0259300



### Active subwoofer system, 50 W

- Compact active subwoofer of elegant design as an addition to compact speakers for hi-fi, PA, home cinema and home recording
- The amplifier features volume control, a phase switch and an automatic switch-on as well as an adjustable crossover frequency (50-250 Hz)
- High-quality bass-reflex MDF cabinet, high-gloss white
- 20 cm (8") bass speaker
- Inputs via 1 x RCA L/R or screw terminals for high-level L/R
- Parallel line out RCA L/R
- Additional outputs high-level L/R for mid-high range speakers. Thus, well suited for connection to already existing speaker lines
- White fabric front cover

Model	ESUB-8F/WS
Total output power	90 W
Power rating (RMS)	50 W
Frequency range	30-250 Hz
Input signal	185 mV/9 k $\Omega$ (RCA L/R) 4 V/480 $\Omega$ (high IN)
Sensitivity	87 dB/W/m
Power supply	~ 230 V/50 Hz/152 VA
Dimensions	300 x 330 x 340 mm
Weight	9.8 kg
Inputs	1 x RCA (L/R), unbal., IN 1 x screw terminals (stereo), high-level IN
Outputs	1 x RCA (L/R) 1 x screw terminals (stereo), high-level OUT