SONIDO

Order No. 1000599





Bluetooth stereo headset

- For universal use
- Bluetooth version V5.0, 2.4 GHz, operating range:
- Wired operation also possible
- Built-in microphone
- Closed system
- Padded ear cushions and headrest
- Accessories include a transport case, 1.3 m connection cable (2 x 3.5 mm plug), 0.6 m charging cable (USB Type-A to micro USB

Model	SONIDO
Transmission method	Bluetooth
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	108 dB/mW
Power supply	built-in 3.7 V rech. Li-ion polymer
	battery 400 mAh
	charging time: approx. 2 hours
	Standby time: approx. 60 hours
	Call time: approx. 15 hours
	Music time: approx. 15 hours
Cable	1.3 m connection cable
	(3.5 mm/3.5 mm)
	0.6 m charging cable (USB Type-A/
	micro USB)
Weight w/o cable	240 g



BH-009

Order No. 0221280

Professional stereo headphones with dynamic boom microphone

- Perfectly closed system for ambient noise suppression
- Excellent sound characteristics, very comfortable to
- Flexible microphone boom, folding, continuously adjustable
- Padded ear cushions and headband
- 2 m cable with single-sided cable inlet and 3.5 mm plugs, supplied with two 6.3 mm adapters

Model	BH-009
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	250 Ω
Headphone sensitivity	117 dB/mW
Transmission range, mic.	120-6,000 Hz
Nominal impedance, microphone	600 Ω
Microphone system	dynamic, cardioid
Microphone sensitivity	1.8 mV/Pa
Cable	2 m, single-sided cable inlet
Plug	2 x 3.5 mm plug
Adapter	2 x 6.3 mm plug
Weight w/o cable	375 g



HP-535

Order No. 0220790

Professional studio monitor headphones

- Excellent sound quality, very comfortable to wear
- Semi-open system, over-ear
- Padded ear cushions and headrest
- 2 m cable with single-sided cable inlet
- 3.5 mm plug with 6.3 mm adapter

Model	HP-535
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	1 W
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	64 Ω
Headphone sensitivity	104 dB/mW
Cable	2 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	380 g



MDH-6300

Order No. 0221090

Mono hand-held DJ headphone

- ullet Powerful neodymium magnet driver Ø 50 mm
- Closed system
- Movable earpiece
- Padded ear cushion
- Ergonomic padded handle
- Removable helix connection cable (1.3-2.8 m) with latchable XLR inline jack and right-angle 6.3 mm stereo plug
- Supplied with transport bag

Model	MDH-6300
Headphone driver	neodymium, Ø 50 mm
Type of transducer	dynamic
Max. input power	3,500 mW
Transmission range, headphones	10-22,000 Hz
Nominal impedance, headphones	46 Ω
Headphone sensitivity	96 dB/mW
Cable	1.3-2.8 m
Plug	6.3 mm plug
Weight w/o cable	152 g

