PAS-254D

Order No. 0179240









Portable amplifier system, for processions and other mobile applications.

- Very comfortable to wear and great mobility due to backpack method
- 1 speaker with 4 speaker chassis
- Class D power amplifier
- Integrated 2-channel multifrequency wireless receiver (TXA-1822MR)
- Bluetooth receiver for wireless connection of mobile audio devices
- Adjustable USB/SD card player with connection for external storage media
- Built-in rechargeable lead gel battery 12 V/7.2 Ah (operating time: up to 7 hours)
- Compartment for spare rechargeable battery to extend operating time
- Integrated automatic battery charging
- Charging socket for supplied charger
- 1 input via comb. jack mic (XLR)/line (6.3 mm), gain control, tone control, mic input with 12 V phantom power
- 1 stereo line input via RCA jacks, gain control, tone control
- MIX OUT output (RCA)
- \bullet Output for a speaker (min. impedance: 4 Ω), either additionally or alternatively to existing speakers
- Adjustable voice over function
- Limiter function
- Nylon backpack with storage pockets

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HT and TXA-800HSE.

Licence-free in the EU.

Model	PAS-254D
Rated power (P _{RMS})	70 W
Peak output power	80 W
Frequency range	80-20,000 Hz
Carrier frequency	863.1-864.9 MHz
Operating range	≈ 100 m
Inputs	2 mV (mic),
	14 mV (line, jack),
	80 mV (line, RCA)
Link	300 mV
Power supply	rech. batt. 12 V/7.2 Ah
Dimensions	Total length: 120 cm
Weight	7.7 kg
Connections	1 x XLR (mic),
	1 x 6.3 mm jack (line),
	1 x RCA L/R (line in),
	1 x RCA L/R (line out),
	1 x USB,
	1 y SPEΔKER



