

Speakers

Speaker Systems

PAB-120WP/SW

Order No. 0253750



Weatherproof high-performance PA speaker system, 120 W

- 2-way bass-reflex system in an ABS cabinet
- 100 V transmission technology
- 30 cm (12") PA bass speaker with impregnated paper cone
- 25 mm (1") horn tweeter system
- Front grille with water-repellent gauze
- Metal parts made of stainless steel
- 4 x M10 threaded insert each at the top and bottom for suspended installation
- Stand sleeve

Model	PAB-120WP/SW
Power rating (RMS)	120/60/30 W
Frequency range	42-20,000 Hz
Number of built-in speakers	2
SPL	98 dB/W/m
Colour	black
Protection class	IP45
Admiss. ambient temp.	-20 °C to +40 °C
Dimensions	370 x 655 x 410 mm
Weight	22.14 kg

- Ball-proof according to DIN 18032, Part 3



EUL-75/WS

Order No. 0162500



PA speaker system

- 100 V transmission technology
- 6-step power selector switch
- Hi-fi full range speaker
- Excellent sound quality
- White grained wooden cabinet with metal front grille
- Floorstanding speaker with wall holder

Model	EUL-75/WS
Power rating (RMS)	10/5/2.5/1.25/0.625 W
Frequency range	70-18,000 Hz
SPL	86 dB/W/m
Dimensions	180 x 290 x 170 mm
Weight	3.7 kg



ESP-315/SW

Order No. 0162860



ESP-315/WS

Order No. 0162870



2-way PA wall-mount speaker systems

- 100 V PA speaker system with an excellent sound
- 2-way system with 10 x 15 cm bass-midrange speaker and 13 mm dome tweeter
- Power taps: 15/10/5/2.5 W
- Power selector switch with 8 Ω operating position
- Can be mounted horizontally or vertically
- Direction of sound radiation can individually be aligned

Model	ESP-315/SW	ESP-315/WS
Total power rating	30 W	30 W
Power rating (RMS)	15/10/5/2.5 W (100 V) 15 W (8 Ω)	15/10/5/2.5 W (100 V) 15 W (8 Ω)
Impedance	8 Ω	8 Ω
Frequency range	75-20,000 Hz	75-20,000 Hz
SPL	90 dB/W/m	90 dB/W/m
Dimensions	Ø 133 mm x 280 mm	Ø 133 mm x 280 mm
Weight	2.1 kg	2.1 kg



MKS-48/WS

Order No. 0132130



Pair of wall/ceiling/corner mount speaker systems, 15 W, 8 Ω

- Universally mountable into most versatile indoor mounting positions
- A cluster with 1-4 elements can optionally be created
- White ABS cabinet
- High-quality 10 cm full range speaker
- Variable support and mounting system

Model	MKS-48/WS
Total power rating	30 W
Power rating (RMS)	15 W
Impedance	8 Ω
Frequency range	100-20,000 Hz
SPL	87 dB/W/m
Dimensions	195 x 145 x 140 mm
Weight	1.5 kg

