

# Speakers

## Speaker Systems

### WALL-05SET/WS

Order No. 0130132



#### Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Mounting bracket for pivoting and tilting

Model	WALL-05SET/WS
Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	80-20,000 Hz
Input signal	500 mV/20 kΩ (unbal.) 660 mV/40 kΩ (bal.)
SPL	89 dB/W/m
Power supply	~ 230 V/50 Hz/100 VA
Dimensions	163 x 252 x 203 mm (with bracket)
Weight	5.5 kg (pair)
Inputs	1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spring-load. speaker term. (passive speaker system) spring-load. speaker term.



### WALL-06SET/WS

Order No. 0130131



#### Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integr. 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- Built-in power supply with 3-pin IEC jack
- 16 cm (6") bass speaker system and dome tweeter

Model	WALL-06SET/WS
Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	70-20,000 Hz
Input signal	890 mV/20 kΩ (unbal.) 1,600 mV/40 kΩ (bal.)
SPL	90 dB/W/m
Power supply	~ 230V/50 Hz/140VA
Dimensions	196 x 303 x 250 mm (with bracket)
Weight	8 kg (pair)
Inputs	1 x RCA L/R (unbalanced) 1 x terminal L/R (balanced) spring-load. speaker term. (passive speaker system) spring-load. speaker term.



- Mounting bracket for pivoting and tilting

### MKA-50SET/SW

Order No. 0132350



### MKA-50SET/WS

Order No. 0132360



#### Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

Model	MKA-50SET/SW, MKA-50SET/WS
Total output power	2 x 40 W
Power rating (RMS)	2 x 20 W
Frequency range	60-20,000 Hz
Input signal	420 mV/24 kΩ
SPL	89 dB/W/m
Power supply	~ 230 V/50 Hz/110 VA
Dimensions	180 x 250 x 160 mm
Weight	5.9 kg (pair)
Inputs	1 x RCA L/R (active speak. system only) 1 x 3.5 mm jack screw terminals (both speaker systems)



### SOUND-4BT/WS

Order No. 0257060



#### Active 2-way stereo speaker system, with

Bluetooth receiver, 2 x 30 W.

- Set consists of an active and a passive bass-reflex speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Bluetooth receiver V4.0 with APTX
- Active speaker system with integrated 2-channel class D amplifier
- Stereo RCA and 3.5 mm jack input, optical digital input (Toslink), mono sub out via RCA jack
- Supplied with remote control
- 10 cm (4") bass speaker and 25 mm (1") dome tweeter
- Excellent sound characteristics with linear adjustment

Model	SOUND-4BT/WS
Power rating (RMS)	2 x 30 W
Frequency range	45-20,000 Hz
Input signal	Bluetooth 500 mV/10 kΩ
SPL	85 dB/W/m (each speaker system)
Power supply	~ 230 V/50 Hz/170 VA
Dimensions	140 x 215 x 170 mm
Weight	5.2 kg (pair)
Inputs	1 x RCA L/R 1 x 3.5 mm stereo jack 1 x Toslink, optical digital input spring-load. speaker term. for passive sp. system



- High-gloss lacquered MDF wooden cabinet of high quality