

Audio Streaming Dante®

WALL-05DTM/WS

Order No. 1000788



Active speaker with integrated Dante® module

- 2-way system
- 13 cm (5") bass-midrange speaker and 13 mm (1/2") tweeter
- Mounting bracket for pivoting and tilting
- Power supply via PoE (Power over Ethernet) or via optional power supply (19 V/2.5 A)

Model	WALL-05DTM/WS
Power rating (RMS)	30 W
Frequency range	62-20,000 Hz
SPL	89 dB/W/m
Power supply	PoE or power supply 19 V/2.5 A (not supplied)
Dimensions	163 x 252 x 165 mm
Weight	2.12 kg
Inputs	1 x RJ45 (Dante® In)
Outputs	1 x RJ45 (feed-through output)



System requirements Dante®: Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

IT-400DT

Order No. 0163870



Weatherproof active horn speaker (music horn), 2-way technology

- With integrated Dante® module and DSP
- DSP-controlled 20 W amplifier
- Power supply via PoE (Power over Ethernet)
- Weatherproof and IP66 certified
- Very wideband sound with a distinct bass volume, even at very high volume levels
- 16 cm bass-midrange speaker and 25 mm (1") horn
- Robust plastic housing
- Supplied with mounting bracket and screws made of stainless steel

Model	IT-400DT
Power rating (RMS)	20 W
Frequency range	100-20,000 Hz
SPL	98 dB/W/m
Beam angle	H: 100°/V: 60°
Admiss. ambient temp.	-20 °C to +50 °C
Power supply	PoE
Dimensions	420 x 335 x 400 mm
Weight	6.12 kg
Inputs	1 x RJ45



System requirements Dante®: Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

ETS-630DT

Order No. 0163490



Active PA column speaker, with integrated Dante® module.

- 30 W class D amplifier
- 6 x 7.6 cm (3") full range speaker
- Decoding: 16/24/32 bits
- Sampling rates: 44.1/48/88.2/96 kHz
- PoE (Power over Ethernet)
- 2 x M12 threaded bushing
- Metal cabinet with white metal front grille
- Supplied with mounting bracket

Model	ETS-630DT
Power rating (RMS)	30 W
Frequency range	120-18,000 Hz
SPL	95 dB/W/m
Beam angle	H: 120°/V: 40°
Power supply	PoE
Dimensions	95 x 610 x 120 mm
Weight	5.57 kg
Inputs	RJ45



System requirements Dante®: Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

EDL-80DT

Order No. 0163480



Active 2-way flush-mount ceiling speaker, with integrated Dante® module.

- 30 W amplifier
- 20 cm (8") bass speaker with glass fibre cone, 2.5 cm (1") dome tweeter
- Decoding: 16/24/32 bits
- Sampling rates: 44.1/48/88.2/96 kHz
- Power supply via PoE (Power over Ethernet)
- Plastic frame and protective metal grille
- For a ceiling thickness up to 4 cm
- Mounting cutout: Ø 240 mm
- Mounting depth: 225 mm incl. space requirement for network connection

Model	EDL-80DT
Power rating (RMS)	30 W
Frequency range	100-20,000 Hz
SPL	93 dB/W/m
Beam angle	100°
Power supply	PoE via RJ45
Dimensions	Ø 272 mm x 187 mm
Weight	2.7 kg
Inputs	RJ45



System requirements Dante®: Windows 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.