

RACK-42NV

Order No. 0257650



RACK-33NV

Order No. 0257640



RACK-21NV

Order No. 0257630



RACK-15NV

Order No. 0257620



Equipment racks for 482 mm (19") devices

- Sheet steel version
- Light grey powder coating (RAL 7035)
- Front door with safety glass and swivel handle lock
- Hinges can easily be changed for door to be opened to the left or to the right
- Side walls and rear wall can be removed and locked
- Supplied with earthing set, 4 levelling feet and 28 mounting kits

RACK-42NV: 42 RU

RACK-33NV: 33 RU

RACK-21NV: 21 RU

RACK-15NV: 15 RU

Image similar.



Model	RACK-42NV	RACK-33NV	RACK-21NV	RACK-15NV
Size	482 mm (19")	482 mm (19")	482 mm (19")	482 mm (19")
Rack units, RU	42	33	21	15
Colour	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)
Mounting accessories	earthing set, 28 mounting kits	earthing set, 28 mounting kits	earthing set, 28 mounting kits	earthing set, 28 mounting kits
Usable depth	590 mm	590 mm	590 mm	590 mm
Outside dimensions	600 x 1,978 x 600 mm	600 x 1,578 x 600 mm	600 x 1,045 x 600 mm	600 x 778 x 600 mm
Max. load capacity	500 kg	300 kg	300 kg	300 kg
Weight	73 kg	55 kg	42 kg	38 kg

RACK-12W

Order No. 0244520



RACK-6W

Order No. 0244540



Wall-mounted housings for 482 mm (19") devices

- Sheet steel version
- Light grey powder coating (RAL 7035)
- Lockable front door with safety glass
- Door can be opened either to the left or to the right
- Side walls and rear wall can be removed and locked
- Maximum mounting depth behind the front plate: 370 mm
- Supplied with earthing set and 16 sets of mounting screws

RACK-12W: 12 RS

RACK-6W: 6 RS

Model	RACK-12W	RACK-6W
Size	482 mm (19")	482 mm (19")
Rack units, RU	12	6
Colour	grey (RAL 7035)	grey (RAL 7035)
Mounting accessories	earthing set, 16 sets of mounting screws	earthing set and 16 sets of mounting screws
Usable depth	380 mm	380 mm
Outside dimensions	600 x 624 x 400 mm	600 x 358 x 400 mm
Max. load capacity	40 kg	40 kg
Weight	24 kg	15 kg



RACK-12WP

Order No. 0244530



RACK-6WP

Order No. 0244550



Wall-mounted housings for 482 mm (19") devices, with movable middle part of the housing.

- Sheet steel version
- Light grey powder coating (RAL 7035)
- Lockable front door with safety glass
- Door can be opened either to the left or to the right
- Side walls and rear wall can be removed and locked
- Max. mounting depth behind the front plate: 470 mm
- Supplied with earthing set and 16 sets of mounting screws

RACK-12WP: 12 RS

RACK-6WP: 6 RS

Model	RACK-12WP	RACK-6WP
Size	482 mm (19")	-
Rack units, RU	12	6
Colour	grey (RAL 7035)	grey (RAL 7035)
Mounting accessories	earthing set, 16 sets of mounting screws	earthing set, 16 sets of mounting screws
Usable depth	490 mm	490 mm
Outside dimensions	600 x 624 x 500 mm	600 x 358 x 500 mm
Max. load capacity	40 kg	40 kg
Weight	26 kg	19 kg

