

Wall-mounted PA Volume Controls with 24 V Emergency Priority Relay

- Attenuation in 10 steps, position 0 is OFF
- For 100 V line technique
- White plastic front panel and knob
- Also suitable for already existing series of switches with standard cover frames (cutout: 50 mm or 55 mm)
- Flush mounting into standard 60 mm wall sockets (ATT-5100PEU into 65 mm wall socket)
- Plug-in screw terminal



Model	Order No.	Frequency range	Power rating	Priority facility	Dimensions	Mounting depth	Weight	Surface-mounted housing
ATT-506PEU	0173890	50-18,000 Hz	6 W	yes	80 x 80 x 67 mm	45 mm	212 g	-
ATT-512PEU	0173900	50-18,000 Hz	12 W	yes	80 x 80 x 67 mm	45 mm	222 g	-
ATT-524PEU	0173910	50-18,000 Hz	24 W	yes	80 x 80 x 66 mm	45 mm	231 g	-
ATT-5100PEU	0173940	50-18,000 Hz	100 W	yes	80 x 80 x 70 mm	50 mm	342 g	-

Wall-Mounted PA Volume Controls with 24 V Emergency Priority Relay

- Attenuation in 10 steps, position 0 is OFF
- For 100 V line technique
- Snow-white plastic front panel and knob
- Flush mounting into standard 65 mm wall sockets (except ATT-3100PEU)
- Surface mounting with matching housing ATT-300, available at option
- Plug-in screw terminal



Model	Order No.	Frequency range	Power rating	Priority facility	Dimensions	Mounting depth	Weight	Surface-mounted housing
ATT-306PEU	0173690	50-18,000 Hz	6 W	yes	80 x 80 x 67 mm	45 mm	97 g	ATT-300
ATT-312PEU	0171380	50-18,000 Hz	12 W	yes	80 x 80 x 67 mm	45 mm	168 g	ATT-300
ATT-324PEU	0171390	50-18,000 Hz	24 W	yes	80 x 80 x 67 mm	45 mm	175 g	ATT-300
ATT-336PEU	0171400	50-18,000 Hz	36 W	yes	80 x 80 x 67 mm	45 mm	234 g	ATT-300
ATT-350PEU	0171410	50-18,000 Hz	50 W	yes	80 x 80 x 67 mm	45 mm	233 g	ATT-300
ATT-3100PEU	0172630	50-18,000 Hz	100 W	yes	80 x 80 x 67 mm	45 mm	335 g	ATT-300

Wall-Mounted PA Volume Controls

- Attenuation in 10 steps, position 0 is OFF
- Audio transformer for 100 V line technique
- White plastic front panel and knob
- Flush mounting, surface mounting with matching housing ATT-200, available at option



Model	Order No.	Frequency range	Power rating	Priority facility	Dimensions	Mounting depth	Weight	Surface-mounted housing
ATT-212/WS	0173670	50-18,000 Hz	12 W	no	85 x 85 x 66 mm	42 mm	156 g	ATT-200
ATT-224/WS	0173680	50-18,000 Hz	24 W	no	85 x 85 x 66 mm	38 mm	154 g	ATT-200
ATT-235/WS	0170580	50-18,000 Hz	35 W	no	85 x 85 x 71 mm	42 mm	212 g	ATT-200
ATT-250/WS	0170590	50-18,000 Hz	50 W	no	85 x 85 x 71 mm	42 mm	211 g	ATT-200
ATT-2100/WS	0172610	50-18,000 Hz	100 W	no	85 x 85 x 71 mm	42 mm	260 g	ATT-200