

### ETS-530TW/SW

Order No. 0162650

100V 8Ω

### ETS-530TW/WS

Order No. 0162660

100V 8Ω

### ETS-515TW/SW

Order No. 0162620

100V 8Ω

### ETS-515TW/WS

Order No. 0162630

100V 8Ω

#### PA column speakers

- 100 V transmission technology or 8 Ω operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8 Ω switching
- 2 x 6 mm threaded bushing
- Plastic cabinet and protective metal grille in black (SW) or white (WS)
- Supplied with mounting bracket
- Connection via spring-loaded speaker terminal



Model	ETS-530TW/SW, ETS-530TW/WS	ETS-515TW/SW, ETS-515TW/WS
Total power rating	60 W	30 W
Power rating (RMS)	30/15/7.5/4/2 W (100 V) 30 W (8 Ω)	15/7.5/4/2/1 W (100 V) 15 W (8 Ω)
Frequency range	85-20,000 Hz	90-20,000 Hz
Number of built-in speakers	4+1	2+1
SPL	89 dB/W/m	87 dB/W/m
Dimensions	128 x 620 x 140 mm	128 x 385 x 140 mm
Weight	4.5 kg	2.8 kg

### ETS-230TW/WS

Order No. 0162110

100V

### ETS-215TW/WS

Order No. 0162100

100V

PA column speakers, in extruded aluminium cabinets, with top and bottom plates of aluminium.

- 100 V transmission technology
- 2-way version (with additional integrated tweeters for a clearly improved sound)
- Integrated crossover network
- 5-step power selector switch
- 2 x M6 threaded bushing
- Metal front grille
- Supplied with mounting brackets
- Connection via cable, 2 cores

ETS-230TW/WS with 4 tweeters  
ETS-215TW/WS with 2 tweeters

Model	ETS-230TW/WS	ETS-215TW/WS
Power rating (RMS)	20/10/5/2.5 W	12/6/3/1.5 W
Frequency range	200-20,000 Hz	250-20,000 Hz
Number of built-in speakers	8+4	4+2
SPL	94 dB/W/m	90 dB/W/m
Dimensions	105 x 700 x 75 mm	105 x 410 x 75 mm
Weight	4.2 kg	2.6 kg



### ETS-230/WS

Order No. 0161310

100V

### ETS-215/WS

Order No. 0161300

100V

PA column speakers, in extruded aluminium cabinets, with top and bottom plates of aluminium.

- 100 V transmission technology
- 5-step power selector switch
- 2 x M6 threaded bushing
- Metal front grille
- Supplied with mounting brackets
- Connection via cable, 2 cores

Model	ETS-230/WS	ETS-215/WS
Power rating (RMS)	30/15/7.5/3.75 W	15/7.5/3.75/2 W
Frequency range	200-15,000 Hz	250-15,000 Hz
Number of built-in speakers	8	4
SPL	95 dB/W/m	92 dB/W/m
Dimensions	105 x 687 x 85 mm	105 x 405 x 85 mm
Weight	3.9 kg	2.5 kg

