

Speakers

Speaker Systems

WALL-08T/SW

Order No. 1000607



WALL-08T/WS

Order No. 1000608



Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 20 cm (8") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Model	WALL-08T/SW	WALL-08T/WS
Total power rating	120 W	120 W
Power rating (RMS)	50/25/12.5/6.25 W (100 V)	50/25/12.5/6.25 W (100 V)
	60 W (8 Ω)	60 W (8 Ω)
Impedance	8 Ω	8 Ω
Frequency range	35-20,000 Hz	35-20,000 Hz
SPL	90 dB/W/m	90 dB/W/m
Protection class	IP65	IP65
Dimensions (with bracket)	245 x 378 x 306 mm	245 x 378 x 306 mm
Weight	5 kg	5 kg
Inputs	spring-load, speaker term.	spring-load, speaker term.



WALL-06T/SW

Order No. 0163600



WALL-06T/WS

Order No. 0163610



Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 16 cm (6") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Model	WALL-06T/SW	WALL-06T/WS
Total power rating	100 W	100 W
Power rating (RMS)	32/16/8/4 W (100 V)	32/16/8/4 W (100 V)
	50 W (8 Ω)	50 W (8 Ω)
Frequency range	70-20,000 Hz	70-20,000 Hz
SPL	90 dB/W/m	90 dB/W/m
Dimensions (with bracket)	196 x 303 x 250 mm	196 x 303 x 250 mm
Weight	3,5 kg	3,5 kg
Inputs	spring-load, speaker term.	spring-load, speaker term.



WALL-05T/SW

Order No. 0163580



WALL-05T/WS

Order No. 0163590



Pairs of 2-way PA speaker systems

- Wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 13 cm (5") bass-midrange speaker and 12 mm (1/2") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Model	WALL-05T/SW	WALL-05T/WS
Total power rating	80 W	80 W
Power rating (RMS)	16/8/4/2 W (100 V)	16/8/4/2 W (100 V)
	40 W (8 Ω)	40 W (8 Ω)
Frequency range	80-20,000 Hz	80-20,000 Hz
SPL	89 dB/W/m	89 dB/W/m
Dimensions (with bracket)	163 x 252 x 203 mm	163 x 252 x 203 mm
Weight	2,6 kg	2,6 kg
Inputs	spring-load, speaker term.	spring-load, speaker term.



WALL-04T/SW

Order No. 0163560



WALL-04T/WS

Order No. 0163570



Pairs of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white (WS) or black (SW)
- 4 power taps as well as switchable to 8 Ω operation
- 10 cm (4") bass-midrange speaker and 12 mm (1/2") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Model	WALL-04T/SW	WALL-04T/WS
Transm. techn.	100 V	100 V
Total power rating	60 W	60 W
Power rating (RMS)	16/8/4/2 W (100 V)	16/8/4/2 W (100 V)
	30 W (8 Ω)	30 W (8 Ω)
Frequency range	90-20,000 Hz	90-20,000 Hz
SPL	87 dB/W/m	87 dB/W/m
Dimensions (with bracket)	130 x 197 x 164 mm	130 x 197 x 164 mm
Weight	1,8 kg	1,8 kg
Inputs	spring-load, speaker term.	spring-load, speaker term.

