Tender text

LR-202

Induction loop receiver,

for receiving audio signals in audio induction loop systems. The electromagnetic field which is created by an induction loop is received by the induction loop receiver and converted into an audio signal. Any number of receivers can be operated within one induction loop.
The unit is suitable for people with and without hearing problems and can be used for various applications:

Hearing aid for the hearing impaired
Operational test of audio induction loop systems
Detection of stray radiation within a loop
Interpretation systems
Lectures in museums, at exhibitions, etc.

• 3.5 mm mono connection fo headphones ≥ 32 Ω
• Volume control
• Low cut switch
• Belt clip
• Power supply via 9 V battery
• Dimensions: 60 x 112 x 35 mm
• Weight: 60 g

Specifications:

Description	inductive receiver
Suitable for	loop amplifiers, sound reproduction systems
Power supply	9 V battery
Admiss. ambient temp.	0-40 °C
Dimensions	60 x 112 x 35 mm
Weight	60 g
Connections	3.5 mm mono jack
Packing unit	1
Packing dimensions (W x H x L)	0.07 x 0.04 x 0.115 m
Gross weight	0.136 kg
Net weight	0.106 kg

Brand: MONACOR

Type: LR-202

Quantity: 1

Packing dimensions (W x H x L): 0.07 x 0.04 x 0.115 m

Gross weight: 0.136 kg

Net weight: 0.106 kg

Item weight (w/o accessories): 0.06 kg