

Tender text

PA-1200M

Monitor unit, 10 + 1 channels

- Audio sources can be selected via rotary switch
- 10 monitor inputs 1-100 V/10 k Ω
- 1 aux input 0 dB (0.775 V)/600 Ω
- Level control, LED VU meter and clip LED for each monitor input
- Built-in 2 W speaker, volume control
- Headphone output
- Mains operation and 24 V emergency power operation

Specifications:

Power rating	2 W
Channels	11
Inputs	1-100 V/10 k Ω (monitor) 0.775 V/600 Ω (aux)
Frequency range	100-20,000 Hz
THD	< 0.3%
Phantom power	
Mains voltage	DC 230 V
Mains frequency	50 Hz
Power consumption, operation	15 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	0.5 A
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	88 mm
Depth	200 mm
Rack spaces, RS	2
Weight	4.7 kg
Connections	screw terminals (monitor input 1-10), screw terminals (aux input), 6.3 mm jack (headphones)
Packing dimensions (W x H x L)	0.34 x 0.175 x 0.55 m
Gross weight	5.86 kg
Net weight	4.8 kg

Brand: MONACOR

Type: PA-1200M

Quantity: 1

Packing dimensions (W x H x L): 0.34 x 0.175 x 0.55 m

Gross weight: 5.86 kg

Net weight: 4.8 kg

Item weight (w/o accessories): 4.7 kg