Tender text

PA-2405

5-zone mono PA mixing amplifier

• 1 x 240 W
• 5 zones, can be controlled individually
• Silent operation due to fanless cooling concept
• Chime/siren, tele-paging, music on hold
• Bass, treble and master controls, status indication via LEDs
• Phantom power for electret microphones
• Connection for zone paging microphone
• Mains operation and 24 V emergency power operation
• 482 mm (19") rack installation with supplied mounting brackets

Specifications:

Peak output power	340 W
Power rating at 16 Ω	
Channels	6
Zones	5
Inputs	1.5 mV/20 kΩ (mic 1-3), 1.5 mV/20 kΩ, 24.5 V/10 kΩ (mic 4-6/line), 0.775 V/10 kΩ (preamplifier)
Frequency range	60-18,000 Hz
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 80 dB
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	630 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 27 A
Admiss. ambient temp.	0-40 °C
Width	420 mm
Height	88 mm
Depth	320 mm
Rack spaces, RS	2
Weight	10.3 kg
Connections	3 x XLR, bal. (mic 1-3), 3 x 6.3 mm jack (mic 4-6) 3 x RCA L/R (line 4-6), 3 x RCA L/R (aux 1-3), 1 x RJ45 (push-to-talk microphone), screw terminals (telephone system), 1 x 6.3 mm jack (preamplifier), 1 x 6.3 mm jack (ext. amplifier), 2 x 6.3 mm jack (link in/out),

screw terminal (speakers)

Brand: MONACOR

Type: PA-2405

Quantity: 1

Packing dimensions (W x H x L):

Gross weight: 11.2 kg

Net weight: 10.3 kg

Item weight (w/o accessories): 10.3 kg