

## Tender text

### PA-2410Z

#### 10-zone mono PA mixing amplifier

- 1 x 240 W
- 10 zones, can be controlled individually
- 3 inputs microphone/line via comb. jacks
- 2 inputs stereo line via RCA jacks
- Chime, continuous sound and wailing sound, automatic mute, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, LEDs for indicating signal/clip, regulated fan
- Insertions for various functions are available at option
- Phantom power for electret microphones
- Connection for up to 3 zone paging microphones PA-2400RC
- Connection for up to 3 push-to-talk microphones PA-4300PTT
- Alarm announcement with insertion PA-1120DMT (available at option)
- Mains operation and 24 V emergency power operation
- Removable mounting brackets

#### Specifications:

Peak output power	290 W
Power rating	240 W
Power rating at 100 V	240 W
Channels	5
Zones	10
Inputs	2.5 mV/5 k $\Omega$ , 0.3 V/5 k $\Omega$ (mic/line 1-3), 0.3 V/15 k $\Omega$ (line 4-5), 0.775 V/100 k $\Omega$ (preamplifier)
Frequency range	55-16,000 Hz
Equalizer bass	$\pm$ 10 dB/100 Hz
Equalizer treble	$\pm$ 10 dB/10 kHz
S/N ratio	> 70 dB (mic), > 80 dB (line)
THD	< 1%
Phantom power	
Mains voltage	~ 230
Mains frequency	50 Hz
Power consumption, operation	700 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 16 A
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	133 mm
Depth	352 mm
Rack spaces, RS	3
Weight	15 kg
Connections	3 x comb. 6.3 mm/XLR (mic/line),

2 x RCA L/R (line),  
1 x 6.3 mm jack (preamplifier input),  
1 x RJ45 (push-to-talk mic),  
1 x RJ45 (zone paging mic),  
screw terminals (speakers),  
1 x RCA L/R (record output)  
1 x 6.3 mm jack (preamplifier output),  
screw terminals (chime button)

Brand: MONACOR

Type: PA-2410Z

Quantity: 1

Packing dimensions (W x H x L): 0.48 x 0.22 x 0.545 m

Gross weight: 18.39 kg

Net weight: 16.75 kg

Item weight (w/o accessories): 15 kg