

Tender text

PA-948

Mono PA mixing amplifier

- 1 x 480 W
- 4 balanced microphone inputs and line inputs with selectable priority
- 4 stereo line inputs
- Speaker outputs via screw terminal contacts
- Balanced line output
- Record output
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- 2-tone or 4-tone chime, can be activated externally
- Input level control and output level control
- 2-way tone control for the output
- Switchable 48 V phantom power for microphone inputs
- Temperature-controlled fan
- Mains operation or 24 V emergency power operation
- Removable mounting brackets

Specifications:

Peak output power	680 W
Power rating	480 W
Channels	5
Inputs	2.5-100 mV (mic), 350 mV (line)
Frequency range	50-16,000 Hz
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 75 dB
THD	< 0.1%
Phantom power	48 V
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,090 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 27 A
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	137 mm
Depth	395 mm
Rack spaces, RS	3
Weight	19 kg
Connections	4 x XLR (mic), 4 x RCA L/R (line), 1 x XLR (line out), 1 x RCA L/R (line out), screw terminals (speakers)

Packing dimensions (W x H x L)	0.525 x 0.26 x 0.565 m
Gross weight	21.96 kg
Net weight	18.81 kg

Brand: MONACOR

Type: PA-948

Quantity: 1

Packing dimensions (W x H x L): 0.525 x 0.26 x 0.565 m

Gross weight: 21.96 kg

Net weight: 18.81 kg

Item weight (w/o accessories): 19 kg