

Tender text

RF-EXPLORER/6

RF spectrum analyser, 15-2,700 MHz, 4,850-6,100 MHz,

in a compact aluminium housing with two antennas (SMA connection) for the different frequency ranges, including to prevent frequency collisions when setting up radio links in the frequency range mentioned above.

- Real-time monitoring of the frequency range used with indication of frequency and level (dBm and dBµV)
- Backlit high-contrast graphic display (128 x 64 pixels)
- Automarker function and manual marker positioning for setting an individual carrier frequency
- Special Wi-Fi analyser with display of 13 WLAN channels
- Max hold function for a reliable detection of ultra-short RF carrier frequencies (additional modes: normal, max., average, overwrite)
- Mini USB 2.0 interface for connection to a PC or laptop as well as for charging the built-in rechargeable lithium polymer battery (1,000 mAh)
- Supplied with transport bag and USB cable
- Client software with real-time analysis for Windows XP/Vista/Win7/Win8.x/Win10/Windows Server (32-bit or 64-bit version) can be downloaded at www.monacor.com
- Dimensions: 71 x 122 x 25 mm
- Weight: 210 g

Specifications:

Display	graphic display (128 x 64 pixels)
Frequency	15-2,700 MHz, 4,850-6,100 MHz
Admiss. ambient temp.	0-40 °C
Dimensions	71 x 122 x 25 mm
Weight	210 g
Power supply	rech. lithium polymer battery, 1000 mAh
Special features	mini USB port

Brand: MONACOR

Type: RF-EXPLORER/6

Quantity: 1

Packing dimensions (W x H x L): 0.12 x 0.05 x 0.17 m

Gross weight: 0.414 kg

Net weight: 0.358 kg

Item weight (w/o accessories): 0.21 kg