

Tender text

STA-1506

6-channel PA amplifier,

with integrated limiter.

- Balanced inputs
- High-pass filter, low-pass filter, can be activated as required for each channel
- Tamper-resistant level adjustment on the rear panel
- 8 Ω bridged operation possible
- LED VU meter and LED per channel for indicating overload (clip)
- Soft start
- Ground lift switch
- Speaker switch-on delay
- Fan cooling
- Protected against short circuit, overheating and DC voltage overlay at the outputs

Specifications:

Peak output power	1,400 W
Power rating	960 W
Power rating at 4 Ω	6 x 160 W
Power rating at 8 Ω	6 x 100 W
Power rating with 8 Ω bridged operation	3 x 320 W
Channels	6
Inputs	0.7 V/20 k Ω
Attenuation factor	
Frequency range	12-20,000 Hz
Crossover network	yes
Crossover frequency	240 Hz
Integrated limiter	yes
S/N ratio	> 80 dB
Crosstalk attenuation	> 60 dB
THD	< 0.1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,800 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	132 mm
Depth	310 mm
Rack units, RU	3
Weight	15.5 kg
Connections	6 x 3-pole XLR, bal. 6 x screw terminal
Packing dimensions (W x H x L)	0.52 x 0.22 x 0.43 m

Gross weight	17.08 kg
Net weight	15.84 kg

Brand: MONACOR

Type: STA-1506

Quantity: 1

Packing dimensions (W x H x L): 0.52 x 0.22 x 0.43 m

Gross weight: 17.08 kg

Net weight: 15.84 kg

Item weight (w/o accessories): 15.5 kg