

Tender text

TXA-800ST

16-channel PLL transmitter,

for microphone operation and line audio signals.

- Matching the receivers TXA-800R, ATS-16R and portable amplifiers of the TXA-800 series, TXA-1020 series
- 16 selectable UHF frequencies (863.1-864.9 MHz)
- Audio stereo line input via RCA L/R
- Balanced XLR microphone input and 6.3 mm microphone input
- Audio mono line output via RCA
- Adjustable headphone output
- Backlit LCD for indicating channel/frequency, LEDs for carrier frequency, signal and signal peak
- Additional DC voltage output 10-15 VDC for connecting an additional transmitter
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.25 kg

Licence-free in the EU.

Specifications:

General information

Description	transmitter unit
Carrier frequency range	863.1-864.9 MHz
Channels	1
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Operating range	approx. 30 m
Power supply transmitter	via encl. plug-in power supply
Width transmitter	215 mm
Height transmitter	50 mm
Depth transmitter	210 mm
Weight transmitter	1.25 kg
Connections transmitter	1 x XLR, bal. (mic in), 1 x 6.3 mm jack, unbal. (mic in), 1 x RCA L/R (line in), 1 x RCA L/R (line out)

Brand: MONACOR

Type: TXA-800ST

Quantity: 1

Packing dimensions (W x H x L): 0.36 x 0.105 x 0.32 m

Gross weight: 1.934 kg

Net weight: 1.417 kg

Item weight (w/o accessories): 1.25 kg