

## Tender text

### TXA-802SR

#### 2-channel multifrequency receiver,

with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-800ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system
- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal
- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg

#### Licence-free in the EU.

Specifications:

##### General information

Description	receiver unit
Carrier frequency range	863.1-864.9 MHz
Channels	2
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	30 mV (XLR), 730 mV (6.3 mm jack, high), 80 mV (6.3 mm jack, low)
Power supply receiver	via encl. plug-in power supply
Width receiver	215 mm
Height receiver	50 mm
Depth receiver	210 mm
Weight receiver	1.2 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

Brand: MONACOR

Type: TXA-802SR

Quantity: 1

Packing dimensions (W x H x L): 0.36 x 0.105 x 0.33 m

Gross weight: 1.82 kg

Net weight: 1.34 kg

Item weight (w/o accessories): 1.2 kg