

Tender text

TXS-2402SET

Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges with supercardioid polar pattern

Licence-free in the EU.

Specifications:

General information

Description	wireless microphone system
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
Channels	2
THD	< 0.1%
Dynamic range	87 dB
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Operating range	approx. 30 m (free field) approx. 20 m (indoors)
Power supply transmitter	
Width transmitter	54 mm
Height transmitter	54 mm
Depth transmitter	225 mm
Weight transmitter	120 g
Specifications receiver	
Audio signal receiver	100 mV/600 Ω
Power supply receiver	via encl. plug-in power supply
Width receiver	220 mm
Height receiver	45 mm
Depth receiver	150 mm
Weight receiver	550 g
Connections receiver	1 x 6.3 mm jack, unbal.

Brand: IMG STAGELINE

Type: TXS-2402SET

Quantity: 1

Packing dimensions (W x H x L): 0.28 x 0.065 x 0.345 m

Gross weight: 1.516 kg

Net weight: 1.066 kg

Item weight (w/o accessories): 1.066 kg