

## Tender text

### TXS-707HT

#### Hand-held microphone with integrated multifrequency transmitter,

with UHF PLL technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 100 selectable UHF frequencies (667.000-691.750 MHz), can be synchronised with receiver TXS-727 or TXS-707 via SYNC function
- Adjustable sensitivity
- Switchable transmitting power (high: 30 mW/low: 2.5 mW)
- Mute function
- LCD for indicating channel, frequency, lock, sensitivity and battery status
- Operating range: 120 m (free field)
- Power supply via 2 x 1.5 V battery AA size (not supplied)

#### There are restrictions or requirements within the EU!

**Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!**

Specifications:

Description	hand-held microphone transmitter
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	667.000-691.750 MHz
Transmitting power	2.5 mW/30 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	> 15 h
Audio frequency range	30-18,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 55 mm x 257 mm
Weight	285 g

Brand: IMG STAGELINE

Type: TXS-707HT

Quantity: 1

Packing dimensions (W x H x L): 0.06 x 0.08 x 0.29 m

Gross weight: 0.37 kg

Net weight: 0.285 kg

Item weight (w/o accessories): 0.285 kg