

Tender text

TXS-865

2-channel diversity UHF PLL receivers,

with REMOSET technology.

- 124 selectable channels in 6 channel groups (506-542 MHz)
- Parallel operation of up to 20 channels
- Diversity system with removable antennas
- Integrated scan function
- Pilot tone squelch and noise squelch
- Attenuator with 2-way switching
- LCD for indicating receiver channel/receiver group, audio level/RF level, mute, lock, active antenna and battery status of the transmitter
- XLR output for each channel, bal.
- 6.3 mm output for mixed signal, bal.
- 482 mm (19") rack installation possible with supplied mounting brackets
- 11 V supply voltage for active antennas or antenna amplifier (e.g. TXS-875B) is available

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Specifications:

General information

Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
Channels	2
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	via encl. power supply
Width receiver	420 mm
Height receiver	54 mm
Depth receiver	230 mm
Weight receiver	2 kg
Connections receiver	2 x XLR, bal., 1 x 6.3 mm jack, bal.

Brand: IMG STAGELINE

Type: TXS-865

Quantity: 1

Packing dimensions (W x H x L): 0.3 x 0.105 x 0.495 m

Gross weight: 2.99 kg

Net weight: 2.32 kg

Item weight (w/o accessories): 2 kg