

Tender text

TXS-875

Multifrequency receiver unit,

with UHF PLL technology.

- 193 selectable UHF frequencies (518-542 MHz)
- True diversity system with removable antennas (BNC connection)
- Auto-scan
- Pilot tone squelch, noise mute
- Selectable lock mode
- LCD for indicating frequency, antenna A/B, RF receiving level, AF audio level, battery status of the transmitter
- XLR output and 6.3 mm output
- Supplied with power supply
- Supplies operating voltage to TXS-875B

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Specifications:

General information

Description	receiver unit
Carrier frequency range	518-542 MHz
Audio frequency range	40-18,000 Hz
Channels	1
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	900 mV/1 k Ω (jack) 150 mV/150 Ω (XLR, bal.)
Power supply receiver	via encl. power supply
Width receiver	211 mm
Height receiver	40 mm
Depth receiver	130 mm
Weight receiver	1.1 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

Brand: IMG STAGELINE

Type: TXS-875

Quantity: 1

Packing dimensions (W x H x L): 0.23 x 0.095 x 0.3 m

Gross weight: 1.262 kg

Net weight: 1.16 kg

Item weight (w/o accessories): 1.1 kg