

CC-143 - Page: 1



CC-143

Order No.: 0342360

PRODUCTINFOS

Connecting terminal from WAGO

- 3-conductor terminal with operating levers
- Individually combinable wires and cross sections from 0.14 to 4 mm²
- Power rating: 450 V/32 A
- Continuous operating temperature: up to 85 °C
- Correct position of the conductor and stripping length can be visually checked due to transparent housing
- Two test slots for any standard test prod
- Of very compact size, thus, ideally suited for the application in confined spaces

TECHNICAL SPECIFICATIONS

| CC-143 | |
|-------------|---------------------|
| Description | connecting terminal |
| Туре | WAGO |
| Quantity | 1 |



CC-143 - Page: 2

CC-143

| Features | operating levers |
|------------------------------|-----------------------------------------------|
| Colour/colour coding | transparent |
| Power rating | 450 V/32 A |
| Dielectric strength | 4 kV |
| Certification | UL, ABS, LR |
| Pole number | 3 |
| Cable inlet | AWG 24-12 |
| Suitable cable cross section | flexible conductors: 0.14-4 mm ² |
| | rigid conductors: up to 0.2-4 mm ² |
| Connection | 3-conductor terminal with operating levers |
| Admiss. ambient temp. | 85 °C |
| Dimensions | 18.7 x 8.3 x 18.6 mm |
| Weight | |