



NAC3MPX-TOPSB

Order No.: 0034165

PRODUCTINFOS

NEUTRIK POWERCON True1 TOP Connectors

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ~ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Robust version with latching device and cable inlet with self-adjusting clamps (plug and inline jack only)
- Self-extinguishing according to UL 94V-0
- Protection class IP65 (NAC3FX-W-TOP and NAC3MX-W-TOP)

NEUTRIK POWERCON True1 TOP panel plug

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ~ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0

TECHNICAL SPECIFICATIONS

NAC3MPX-TOPSB

Description	panel plug
Type	NEUTRIK POWERCON TOP
Quantity	1
Features	latching device
Colour/colour coding	black
Power rating	~ 250 V/16 A
Insulating resistance	> 100 MΩ
Dielectric strength	DC 4 kV/~ 2.8 kV
Certification	UL, VDE
Connection	blade terminals, 6.35 mm
Material	plastic
No. of contacts	2
Admiss. ambient temp.	-30-+80 °C
Dimensions	26 x 31 x 38.2 mm
Weight	11 g