



## AN2075/8

Order No.: 1001114

### PRODUCTINFOS

#### Hi-fi full range speaker, 20 W, 8 $\Omega$

- Square basket for tight connection of the speakers used in array applications
- Integrated waveguide (dual cone) for an improved radiation of high frequencies
- Robust aluminium cone
- Half-roll elastomer surround
- Weatherproof

#### Manufacturer information:

Celestion International Ltd  
Claydon Business Park, Great Blakenham,  
Ipswich  
Suffolk IP6 0NL  
United Kingdom  
info@celestion.com

#### Importer:

MONACOR INTERNATIONAL GmbH & Co. KG  
Zum Falsch 36  
28307 Bremen  
Deutschland  
info@monacor.com

## TECHNICAL SPECIFICATIONS

### AN2075/8

Impedance (Z)	8 $\Omega$
Transmission technology	cable
Frequency range	160-19,000 Hz
Resonant frequency (fs)	153.4 Hz
Power rating (RMS)	20 W
Peak music power output (MAX)	40 W
SPL	80 dB/W/m
Suspension compl. (Cms)	0.72 mm/N
Moving mass (Mms)	1.49 g
Mech. Q factor (Qms)	5.281
Electr. Q factor (Qes)	0.998
Total Q factor (Qts)	0.839
Equivalent volume (Vas)	1.5 l
DC resistance (Re)	5.33 $\Omega$
Force factor (BxL)	2.71 Tm
Voice coil induct. (Le)	0.04 mH
Voice coil diameter	$\varnothing$ 20 mm
Voice coil winding height	6 mm
Voice coil former	polyimide
Linear excursion ( $X_{MAX}$ )	$\pm$ 2.25 mm
Eff. cone area (Sd)	12.56 cm <sup>2</sup>
Mounting cutout	$\varnothing$ 51.1 mm
Mounting depth	43.5 mm
Mounting hole diameter	$\varnothing$ 62 mm
Dimensions	56.2 x 56.2 x 43.5 mm
Width	56.2 mm
Height	56.2 mm
Depth	43.5 mm
Colour	black

**AN2075/8**

Admiss. ambient temp.	0-40 °C
Weight	0.1 kg
Packing unit	1
Type of speaker	2"
Packaging dimensions (W x H x L)	0.088 x 0.06 x 0.088 m
Gross weight	0.125 kg
Net weight	0.1 kg

**AN2075/8**

EAN code	739894581950
Net weight	0.1 kg