



SPE-230BT

Order No.: 0163320

PRODUCTINFOS

This high-quality Bluetooth audio system

consists of an active ceiling speaker and a passive ceiling speaker with Bluetooth receiver and serves as a plug-and-play stereo pair for background PA applications.

A robust ABS housing with moisture-resistant bass speaker and coaxially mounted tweeter as well as the magnetically attached metal protective grille and the excellent workmanship all ensure an overall high-quality appearance and optimum handling.

The frameless speaker grille allows for an unobtrusive appearance when mounted into the ceiling or wall.

A wireless connection between audio players like smartphones, tablets, PCs, Android devices or Apple devices such as iPads or iPhones can be established via Bluetooth 4.0 technology. A new initialisation is not required. Depending on the room, the operating range can be up to 10 m.

To save power, the integrated amplifier switches to standby mode in case of inactivity.

Bluetooth hi-fi flush-mount speaker stereo set,

consists of a 2-way active speaker with integrated amplifier, Bluetooth module and crossover network, a 2-way passive speaker with crossover network as well as a matching power supply.

- Pair of 2-way hi-fi speakers for wall mounting and ceiling suspension
- 13 cm (5¼") bass-midrange speaker, 2.54 cm (1") coaxial tweeter

- Master/slave mode (active speaker and passive speaker are combined to create a stereo pair)
- Active speaker with integrated class D amplifier module, 2 x 20 W
- Bluetooth 4.0, APTX
- Operating range: 10 m, class 1
- High-quality crossover network
- Frameless protective metal grille, magnetically attached
- Quick-mount system
- 4-digit PIN code for initial linking
- Recognition of devices which have previously been linked
- 230 V power supply with earthed plug and plug-in connector for active speaker

TECHNICAL SPECIFICATIONS

SPE-230BT

Active/passive	active/passive
Transmission technology	Bluetooth
Power rating (RMS)	2 x 20 W
Frequency range	50-20,000 Hz
Input signal	Bluetooth
System	2-way
Bass speaker	13 cm (5¼") bass-midrange speaker
Midrange speaker	see bass speaker
Tweeter	2.54 cm (1") tweeter
Speaker size	13 cm
SPL	89 dB/W/m
Max. rated SPL	105 dB
Housing material	plastic
Mounting device	quick-mount system
Admiss. ambient temp.	0-40 °C
Power supply	encl. power supply
Dimensions	Ø 205 mm x 90 mm
Width	Ø 205 mm
Depth	90 mm
Weight	1.26 kg (active speak.) 1.18 kg (passive speak.)
Inputs	Bluetooth
Other features	Bluetooth 4.0, class 1 PIN: 0101
Packing dimensions (W x H x L)	0.27 x 0.29 x 0.36 m

SPE-230BT

Gross weight 4.62 kg

Net weight 2.87 kg