



SPH-176

Order No.: 0104250

PRODUCTINFOS

High-quality hi-fi bass-midrange speaker, 70 W, 8 Ω

- Coated paper cone, yet high pulsed power
- Rubber surround
- Bass-optimised drive characteristics
- Allows for setting up speaker systems of highest level stability with an amazingly deep bass reproduction
- Ideally suited for various applications, from 2-way hi-fi speakers and attractive dual bass arrangements to very small subwoofers

TECHNICAL SPECIFICATIONS

SPH-176

Impedance (Z) 8Ω

Frequency range f3-4,500 Hz

Resonant frequency (fs) 39 Hz Power rating (RMS) 70 W



SPH-176

Peak music power output (MAX) 120 W

SPL 90 dB/W/m

Suspension compl. (Cms) 1.01 mm/N

Moving mass (Mms) 14 g

Mech. Q factor (Qms) 2.27

Electr. Q factor (Qes) 0.44

Total Q factor (Qts) 0.37

Equivalent volume (Vas) 27 I

DC resistance (Re) $\,$ 6.6 Ω

Force factor (BxL) 7.70 Tm

Voice coil induct. (Le) 0.75 mH

Voice coil diameter Ø 25 mm

Voice coil former aluminium

Linear excursion (X_{MAX}) \pm 5.5 mm

Eff. cone area (Sd) 140 cm²

Magnet weight 450 g

Magnet diameter Ø 90 mm

Mounting cutout Ø 144 mm

Mounting depth 68 mm

Dimensions Ø 175 mm x 75 mm

Ø 175 mm

Width Ø 175 mm

Depth 75 mm

Outside diameter

Colour black

Admiss. ambient temp. 0-40 °C

Weight 1.23 kg

Packing unit 1

Type of speaker 6.75"

Packing dimensions (W x H x L) 0.195 x 0.1 x 0.195 m

Gross weight 1.34 kg

Net weight 1.23 kg