



DT-25N

Order No.: 0104010

PRODUCTINFOS

Neodymium hi-fi tweeter, 40 W, 8 Ω

- Outstanding sound characteristics
- Silk soft dome cone with optimised geometry
- Front plate with a specially adapted design
- Very linear reproduction even of lower frequencies
- High efficiency
- Low magnetic dispersion and mechanically very compact due to the application of a high-performance neodymium magnet
- Ideally suited for building smaller speaker systems
- For high-quality floorstanding hi-fi speakers, e.g. in D'Appolito arrangements
- Very fine and natural sound

TECHNICAL SPECIFICATIONS

DT-25N

Impedance (Z)	8 Ω
Frequency range	fx-20,000 Hz

DT-25N

Resonant frequency (fs)	1,600 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating (RMS)	40 W
Peak music power output (MAX)	80 W
SPL	95 dB/W/m
Voice coil diameter	Ø 25 mm
Magnet diameter	Ø 46 mm
Mounting cutout	Ø 50 mm
Mounting depth	17.7 mm
Dimensions	Ø 66 x 21 mm
Outside diameter	Ø 66 mm
Width	Ø 66 mm
Depth	21 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.065 kg
Packing unit	1
Packing dimensions (W x H x L)	0.075 x 0.03 x 0.075 m
Gross weight	0.085 kg
Net weight	0.065 kg