

HT-22/8 - Page: 1



HT-22/8

2 20W

Order No.: 0100180

PRODUCTINFOS

Cone tweeter, 10 W, 8 Ω

• Classic tweeter for hi-fi, car hi-fi and for replacement purposes

Klang+Ton 02/2012

"The unit at the most favourable price was the surprise in the test ... provides the most balanced frequency response in front of the microphone ... very attractive price, to be used without any problems, offers best measured values."

Klang+Ton 02/2018

"Quite respectable. [...] considering the modest use of material, a remarkable performance." (SP-13/4 and HT-22/8 in the Cheap Trick 296 of Klang+Ton)

TECHNICAL SPECIFICATIONS

HT-22/8 - Page: 2

HT-22/8	
Impedance (Z)	8 Ω
Frequency range	fx-19,000 Hz
Resonant frequency (fs)	1,500 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,500 Hz
Power rating (RMS)	10 W
Peak music power output (MAX)	20 W
SPL	91 dB/W/m
Voice coil diameter	Ø 12 mm
Magnet diameter	Ø 45 mm
Mounting cutout	Ø 63 mm
Mounting depth	27.4 mm
Mounting hole diameter	Ø 80 mm
Hole spacing X-axis	56 mm
Hole spacing Y-axis	56 mm
Dimensions	Ø 90 mm x 28 mm
Outside diameter	Ø 90 mm
Width	Ø 90 mm
Depth	28 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.14 kg
Packing unit	1
Type of speaker	2"
Packing dimensions (W x H x L)	0.095 x 0.035 x 0.095 m
Gross weight	0.154 kg
Net weight	0.14 kg