



80 W

RBT-1000

Order No.: 0101610

PRODUCTINFOS

Ribbon tweeter for PA and hi-fi, 40 W, 6 Ω

- Magnetostatic speaker with waveguide
- Tweeter system from the L-RAY/1000
- Fine and brilliant reproduction of the high frequencies
- For use from 3,000 Hz (hi-fi) or 4,000 Hz (PA) on via 12 dB filter
- Diecast aluminium horn front attachment, neodymium magnet
- Vertical or horizontal mounting possible due to square front panel
- Installation into a sealed airtight housing is recommended

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

RBT-1000

Impedance (Z)	6 Ω
Transmission technology	cable
Frequency range	fx-22,000 Hz
Resonant frequency (fs)	1.6 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	> 3,000 Hz
Power rating (RMS)	40 W
Peak music power output (MAX)	80 W
SPL	96 dB/W/m
DC resistance (Re)	6 Ω
Magnet diameter	magnetostatic speaker
Mounting cutout	89 x 76 mm
Mounting depth	24 mm
Hole spacing X-axis	87 mm
Hole spacing Y-axis	87 mm
Dimensions	104 x 104 x 24 mm
Width	104 mm
Height	104 mm
Depth	24 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.24 kg
Packing unit	1
Packaging dimensions (W x H x L)	0.12 x 0.04 x 0.12 m
Gross weight	0.263 kg
Net weight	0.237 kg

RBT-1000

EAN code	4007754226898
Net weight	0.237 kg