



SPX-20M

Order No.: 0100930

PRODUCTINFOS

Miniature hi-fi full range speaker, 15 W, 8 Ω

- Round steel basket with rear-ventilated centering spider
- Adhesive mounting or clamp mounting
- Inverse laminated cone
- Efficient neodymium drive system
- Perfect full range reproduction with an excellent efficiency in relation to its size
- 25 mm voice coil of high power capability

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

SPX-20M

| | |
|----------------------------------|-------------------------------|
| Impedance (Z) | 8 Ω |
| Transmission technology | cable |
| Frequency range | f3-22,000 Hz |
| Resonant frequency (fs) | 157 Hz |
| Power rating (RMS) | 15 W |
| Peak music power output (MAX) | 30 W |
| SPL | 87 dB/W/m |
| Suspension compl. (Cms) | 0.76 mm/N |
| Moving mass (Mms) | 1.3 g |
| Mech. Q factor (Qms) | 4.52 |
| Electr. Q factor (Qes) | 0.46 |
| Total Q factor (Qts) | 0.42 |
| Equivalent volume (Vas) | 0.2 l |
| DC resistance (Re) | 6.9 Ω |
| Force factor (BxL) | 4.50 Tm |
| Voice coil induct. (Le) | 0.13 mH |
| Voice coil diameter | \varnothing 25 mm |
| Voice coil former | Kapton |
| Linear excursion (X_{MAX}) | \pm 0.5 mm |
| Eff. cone area (Sd) | 13 cm ² |
| Magnet weight | neodymium |
| Magnet diameter | \varnothing 39 mm |
| Mounting cutout | \varnothing 51.5 mm |
| Mounting depth | 33.5 mm |
| Dimensions | \varnothing 57 mm x 37.5 mm |
| Outside diameter | \varnothing 57 mm |
| Width | \varnothing 57 mm |
| Height | \varnothing 57 mm |
| Depth | 37.5 mm |
| Colour | black/silver |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 0.17 kg |
| Packing unit | 1 |
| Type of speaker | 2" |
| Packaging dimensions (W x H x L) | 0.06 x 0.045 x 0.06 m |

SPX-20M

Gross weight 0.185 kg

Net weight 0.172 kg

SPX-20M

EAN code 4007754217001

Net weight 0.172 kg