



SP-12A/302PA



Order No.: 0104930

PRODUCTINFOS

PA bass-midrange speaker, 300 W, 8 Ω

- Of very high power capability
- 30 cm (12") professional speaker of long excursion
- Diecast basket
- Cone with water-repellent coating
- Very neat workmanship with front-facing basket
- Wide frequency response of low distortion
- High efficiency
- Excellent bass reproduction
- Drive system with drilled pole core and additional magnet for optimising the magnetic field and impedance linearisation
- For bass-reflex cabinets from 30 litres on already
- For all kinds of professional and semiprofessional PA applications

HOBBY HiFi 05/2013

"With the SP-12A/302PA, IMG Stage Line offers a bass speaker of high power capability for 3-way systems which features an impressively deep bass, a superior level stability and an excellent sound quality."



TECHNICAL SPECIFICATIONS

SP-12A/302PA

Impedance (Z) 8 Ω

Frequency range f3-4,000 Hz

Resonant frequency (fs) 50 Hz

Power rating (RMS) 300 W

Peak music power output (MAX) 600 W

SPL 99 dB/W/m

Suspension compl. (Cms) 0.19 mm/N

Moving mass (Mms) 50 g

Mech. Q factor (Qms) 7.87

Electr. Q factor (Qes) 0.35

Total Q factor (Qts) 0.34

Equivalent volume (Vas) 77 I

DC resistance (Re) 6.4 Ω Force factor (BxL) 16.98 Tm

Voice coil induct. (Le) 0.8 mH Voice coil diameter Ø 66 mm Voice coil former Kapton Linear excursion (X_{MAX}) \pm 5 mm Eff. cone area (Sd) 530 cm²

Magnet weight2 kgMagnet diameterØ 154 mmMounting cutoutØ 284 mm

Mounting depth 123 mm

Dimensions Ø 313 mm x 135 mm

Outside diameter Ø 313 mm Width Ø 313 mm Depth 135 mm Colour black 0-40 °C Admiss. ambient temp. Weight 5.1 kg Packing unit 1 Type of speaker 12"

Packing dimensions (W x H x L) 0.345 x 0.165 x 0.345 m

Gross weight 5.8 kg
Net weight 5.1 kg

