



## LR-202

Order No.: 0176370

### PRODUCTINFOS

#### Induction loop receiver,

for receiving audio signals in audio induction loop systems. The electromagnetic field which is created by an induction loop is received by the induction loop receiver and converted into an audio signal. Any number of receivers can be operated within one induction loop.

The unit is suitable for people with and without hearing problems and can be used for various applications:

Hearing aid for the hearing impaired  
Operational test of audio induction loop systems  
Detection of stray radiation within a loop  
Interpretation systems  
Lectures in museums, at exhibitions, etc.

- 3.5 mm mono connection for headphones  $\geq 32 \Omega$
- Volume control
- Low cut switch
- Belt clip
- Power supply via 9 V battery
- Dimensions: 60 x 112 x 35 mm
- Weight: 60 g

## TECHNICAL SPECIFICATIONS

### LR-202

Description	inductive receiver
Suitable for	loop amplifiers, sound reproduction systems
Power supply	9 V battery
Admiss. ambient temp.	0-40 °C
Dimensions	60 x 112 x 35 mm
Weight	60 g
Connections	3.5 mm mono jack
Packing unit	1
Packing dimensions (W x H x L)	0.07 x 0.045 x 0.115 m
Gross weight	0.136 kg
Net weight	0.106 kg