



PA-1120DMT

Order No.: 0174580

PRODUCTINFOS

Digital message and timer insertion,

for PA mixing amplifiers with insertion compartment.

- Backlit DOT matrix display with 2 x 8 digits
- DCF77 synchronised clock (radio-controlled clock) for time-controlled announcements
- Internal memory for up to 26 audio files
- Audio files can be copied to the internal memory via integrated micro SD card reader
- 6 memory recall buttons, memory presets can also be accessed via floating contacts or via zone paging microphone PA-1120RC or PA-6000RC
- 3.5 mm connection on the front panel for picking up microphone signals or line signals
- Up to 20 daily events can be programmed

What is the maximum audio file size on a micro SD memory card?

The maximum file size per memory location (M1 to M6) must not exceed 2176 kByte.

TECHNICAL SPECIFICATIONS

PA-1120DMT

Description	digital message and timer insertion
Colour	black
Suitable for	PA mixing amplifiers with insertion compartment

PA-1120DMT

Power supply	DC 15-17 V/150 mA
Admiss. ambient temp.	0-40 °C
Dimensions	194 x 40 x 85 mm
Weight	270 g
Connections	3.5 mm jack
Other features	integrated micro SD card reader
Packing unit	1
Packaging dimensions (W x H x L)	0.175 x 0.06 x 0.225 m
Gross weight	0.524 kg
Net weight	0.431 kg