



EDL-62HQ

Order No.: 0163430

PRODUCTINFOS

PA hi-fi wall and ceiling speaker, 30 W

- 100 V transmission technology or 8 Ω operation
- 2-way version with coaxial dome tweeter
- 16 cm (6½") bass speaker with waveguide and 25 mm (1") silk dome
- Pivoting tweeter via ball joint
- Excellent sound characteristics
- Stylish flush fit protective metal grille with slim plastic frame
- Protective grille magnetically attached to speaker front
- For a wall thickness/ceiling thickness from 6 to 35 mm

TECHNICAL SPECIFICATIONS

EDL-62HQ

Impedance (Z)	8 Ω
Transmission technology	100 V or low-impedance
Frequency range	50-20,000 Hz

EDL-62HQ

Resonant frequency (fs)	60 Hz
Power rating (RMS)	35 W (8 Ω) 30/16/8/4 W (100 V)
Peak music power output (MAX)	70 W
SPL	89 dB/W/m
Mounting cutout	Ø 210 mm
Mounting depth	97 mm
Dimensions	Ø 250 mm x 98 mm
Outside diameter	Ø 250 mm
Width	Ø 250 mm
Depth	98 mm
Colour	white/black
Admiss. ambient temp.	0-40 °C
Weight	1.82 kg
Packing unit	1
Type of speaker	165
Packing dimensions (W x H x L)	0.27 x 0.13 x 0.27 m
Gross weight	2.15 kg
Net weight	1.82 kg