



EDL-435/WS

Order No.: 0163460

PRODUCTINFOS

High-quality 2-way PA pendant speaker

- 100 V transmission technology
- 2-way coaxial system
- High-quality sound for speech and music
- White ABS bass-reflex housing with steel grille
- 5 m connection cable with canopy

TECHNICAL SPECIFICATIONS

EDL-435/WS

Active/passive	passive
Transmission technology	100 V
Power rating (RMS)	30/20/15/10/5 W
Impedance	8 Ω
Frequency range	80-20,000 Hz (-10 dB) 70-20,000 Hz (-20 dB)

EDL-435/WS

Number of speakers	2
Speaker size	12 cm
SPL	91 dB/W/m
Max. rated SPL	106 dB
Radiation angle/beam angle	125° @1,600 Hz
Radiation angle, horizontal	125°
Radiation angle, vertical	125°
Housing material	ABS
Colour	white
Mounting device	ceiling flange
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 185 mm x 230 mm
Width	Ø 185 mm
Height	230 mm
Weight	2.22 kg
Packing dimensions (W x H x L)	0.31 x 0.3 x 0.32 m
Gross weight	2.84 kg
Net weight	2.22 kg