



EPS32

Order No.: 1000870

PRODUCTINFOS

Amplifier, 2 x 15 W

- For mounting onto DIN rails according to DIN EN 60529, 2 HP
- 2-channel class D amplifier
- Selectable mode stereo/bridged
- Inputs to be switched externally
- Balanced and unbalanced input
- Summing amplifier input
- Microphone input
- Separate volume control for each channel
- High-efficiency green design

TECHNICAL SPECIFICATIONS

EPS32

Peak output power	30 W
Power rating	24 W
Power rating at 4 Ω	2 x 12 W

EPS32

Power rating at 8 Ω	2 x 6 W
Power rating with 4 Ω bridged operation	1 x 24 W
Power rating with 8 Ω bridged operation	1 x 12 W
Output impedance	4-8 Ω
Channels	2
Inputs	1 V/47 k Ω (bal.), 22 k Ω (unbal.)
Frequency range	42-21,000 Hz
S/N ratio	92 dB
THD	0.05%
Phantom power	9-12 V
Operating voltage (possible alternative)	DC 12-26 V, rec. DC 24 V
Admiss. ambient temp.	-20 °C to +40 °C
Width	36 mm
Height	101 mm
Depth	62 mm
Weight	98 g
Connections	spring-loaded terminals
Packaging dimensions (W x H x L)	0.037 x 0.095 x 0.075 m
Gross weight	0.1297 kg
Net weight	0.098 kg

EPS32

EAN code	4007754418491
Net weight	0.098 kg