



PA-4120D

Order No.: 1000015

PRODUCTINFOS

4-channel class D PA power amplifier

- 4 x 120 W
- Class D concept with a high efficiency to cut energy costs
- Temperature-controlled fan, continuously adjustable
- Connection for external on/off switch
- Connection for external mute switch
- LED indication for protect, peak, signal and 100 V/4 Ω operation

TECHNICAL SPECIFICATIONS

PA-4120D

Power rating	480 W
Power rating at 4 Ω	4 x 120 W
Power rating at 100 V	4 x 120 W
Output impedance	100 V/83 Ω, 4 Ω
Channels	4
Inputs	775 mV/20 kΩ, bal.
Frequency range	80-16,000 Hz
S/N ratio	> 95 dB(A)
THD	< 0.1%
Power supply	~ 230 V/50 Hz/850 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz

PA-4120D

Power consumption, operation	850 VA
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	52 mm
Depth	320 mm
Rack units, RU	1
Weight	5.1 kg
Connections	screw contacts (inputs), screw contacts (speakers)
Packing dimensions (W x H x L)	0.54 x 0.14 x 0.39 m
Gross weight	6.05 kg
Net weight	5.12 kg