



STA-450D

Order No.: 0252350

PRODUCTINFOS

4-channel class D amplifier

- Silent operation due to fanless cooling concept
- 8 Ω bridged operation possible
- Mute function for each channel
- 4 level controls
- 1 LED per channel for indicating overload (clip)
- Protected against short circuit

TECHNICAL SPECIFICATIONS

STA-450D

Peak output power	300 W
Power rating	200 W
Power rating at 4 Ω	4 x 50 W
Power rating at 8 Ω	4 x 30 W
Power rating with 8 Ω bridged operation	2 x 100 W
Channels	4
Inputs	1 V/20 k Ω unbal. 550 mV/20 k Ω bal.
Frequency range	10-20,000 Hz

STA-450D

Crosstalk attenuation	> 45 dB
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	300 VA
Admiss. ambient temp.	0-40 °C
Width	~ 483 mm
Height	90 mm
Depth	330 mm
Rack spaces, RS	2
Weight	8.4 kg
Connections	4 x XLR, bal.
	4 x RCA
	4 x spring-load. speaker term. L/R
Packing dimensions (W x H x L)	0.4 x 0.17 x 0.56 m
Gross weight	11 kg
Net weight	8.46 kg