



SA-50

Order No.: 25.4620

Price upon request

PRODUCTINFOS

Compact universal stereo amplifier, 25 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

TECHNICAL SPECIFICATIONS

SA-50

Peak output power	2 x 25 W
Power rating	25 W
Power rating at 4 Ω	2 x 12.5 W
Power rating at 8 Ω	2 x 10 W
Channels	2

SA-50

Inputs	115 mV/12 k Ω (PC),
	115 mV/12 k Ω (CD),
	115 mV/12 k Ω (aux),
	115 mV/12 k Ω (player, high),
	20 mV/32 k Ω (player, low)
Frequency range	20-20,000 Hz
Equalizer bass	\pm 12 dB
Equalizer treble	\pm 12 dB
S/N ratio	> 65 dB
Mains voltage	\sim 230 V
Mains frequency	50 Hz
Power consumption, operation	50 VA
Admiss. ambient temp.	0-40 °C
Width	212 mm
Height	56 mm
Depth	200 mm
Weight	1.8 kg
Connections	1 x RCA L/R (PC),
	1 x RCA L/R (CD),
	1 x RCA L/R (aux),
	1 x 3.5 mm jack (player),
	4 x spring-load. speaker term. (speakers)