



## MMA-130

Order No.: 1000236

### PRODUCTINFOS

The MMA-130 is a mono class D mixing amplifier with 30 W (8 Ω). The device has been developed in-house according to the specifications of a globally operating crane manufacturer and thus is perfectly matched to the application in the crane operator's cabin. The MMA-130 is used for the crane operator's announcements made to people within the pivoting range of the crane.

The compact dimensions of the amplifier which are matched to the dimensions of a standard slot in a motor vehicle and the voltage supply of DC 12-24 V allow for a wide range of additional applications.

The temperature range from -25 °C to +50 °C required for the area of application can easily be realised due to the selected components.

#### **Mono class D PA mixing amplifier,**

30 W/8 Ω.

- 1 microphone input and 1 line input, adjustable
- Line input each on the front panel and rear panel
- Bass and treble controls
- Mute switch
- LED indication for mute and operation
- Standard mounting dimensions (suitable for slots in motor vehicles)
- Power supply: DC 12-24 V

## TECHNICAL SPECIFICATIONS

### MMA-130

Peak output power	30 W
Power rating	30 W
Power rating at 4 $\Omega$	15 W
Power rating at 8 $\Omega$	30 W
Channels	2
Inputs	1.9 mV/560 $\Omega$ (mic), 220 mV/4.8 k $\Omega$ (line)
Frequency range	20-20,000 Hz
Equalizer bass	$\pm$ 12 dB
Equalizer treble	$\pm$ 12 dB
THD	< 0.11%
Power supply	DC 12-24 V/1.5 A
Admiss. ambient temp.	-25 $^{\circ}$ C to +50 $^{\circ}$ C
Width	200 mm
Height	56 mm
Depth	125 mm
Weight	724 g
Connections	1 x XLR (mic input), 2 x RCA L/R (line input), 1 x 2-pole plug-in screw terminal (speakers)
Packaging dimensions (W x H x L)	0.2 x 0.055 x 0.125 m
Gross weight	0.936 kg
Net weight	0.724 kg