



## PA-306

Order No.: 17.6800

**Price upon request**

### PRODUCTINFOS

#### Mono PA mixing amplifier

- 1 x 60 W
- Silent operation due to fanless cooling concept
- 3 microphone inputs, one of which is a balanced input
- Mic 1/line 1 with adjustable input sensitivity, priority circuit and adjustable automatic talkover
- 2 aux inputs
- 1 telephone input for telephone systems with audio output
- Speaker outputs via screw terminals
- 1 line output
- Input and output level controls
- 2-way tone control for the output
- 48 V phantom power for channel 1, can be activated as required
- 482 mm (19") rack installation with supplied mounting brackets

### TECHNICAL SPECIFICATIONS

#### PA-306

Peak output power	80 W
Power rating	60 W
Channels	1

**PA-306**

	6 mV/600 $\Omega$ (mic),
Inputs	310 mV/10 k $\Omega$ (aux), 1 V/10 k $\Omega$ (telephone)
Frequency range	50-16,000 Hz
Equalizer bass	$\pm 10$ dB/100 Hz
Equalizer treble	$\pm 10$ dB/10 kHz
S/N ratio	66 dB (mic) 80 dB (aux)
THD	< 0.5%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	250 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	430 mm
Height	88 mm
Depth	335 mm
Rack spaces, RS	2
Weight	6.7 kg
Connections	1 x 6.3mm/XLR (combo), 1 x 6.3 mm jack (mic1), 2 x 6.3 mm jack (mic 2-3), 2 x RCA L/R (aux 1-2), Screw terminals (telephone), 1 x RCA L/R (line out)