



## PA-324

Order No.: 0174420

### PRODUCTINFOS

#### Mono PA mixing amplifier

- 1 x 240 W
- 3 microphone inputs, one of which is a balanced input
- Mic 1/line 1 with adjustable input sensitivity, priority circuit and adjustable automatic talkover
- 2 stereo line inputs
- 1 telephone input for telephone systems with audio output
- Speaker outputs via screw terminal contacts
- 1 line output
- Input and output level controls
- 2-way tone control for the output
- 48 V phantom power for channel 1, can be activated as required
- 482 mm (19") rack installation with supplied mounting brackets

### TECHNICAL SPECIFICATIONS

#### PA-324

Peak output power	340 W
Power rating	240 W
Channels	input channels:1 output channels: 6

**PA-324**

Inputs	5 mV/600 $\Omega$ (mic), 350 mV/10 k $\Omega$ (aux), 1 V/10 k $\Omega$ (telephone)
Frequency range	50-16,000 Hz
Equalizer bass	$\pm$ 10 dB/100 Hz
Equalizer treble	$\pm$ 10 dB/10 kHz
S/N ratio	66 dB (mic) 80 dB (aux)
THD	< 0.5%
Phantom power	48 V
Power supply	$\sim$ 230 V/50 Hz/740 VA
Mains voltage	$\sim$ 230 V
Mains frequency	50 Hz
Power consumption, operation	740 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	430 mm
Height	88 mm
Depth	380 mm
Rack units, RU	2
Weight	11.6 kg
Connections	1 x 6.3 mm/XLR (combo), 1 x 6.3 mm jack (mic 1), 2 x 6.3 mm jack (mic 2-3), 2 x RCA L/R (aux 1-2), screw terminal (telephone), 1 x RCA L/R (line out), screw contacts (speakers)
Packing dimensions (W x H x L)	0.505 x 0.185 x 0.54 m
Gross weight	14.68 kg
Net weight	11.63 kg