



PA-803DAP

S DAB+ 100V 4Ω 8Ω 16Ω BT

Order No.: 1000168

PRODUCTINFOS

Mono class D PA mixing amplifier,

with integrated MP3 player, FM/DAB+ tuner and Bluetooth.

- 1 x 30 W
- Class D concept with high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- Bluetooth version 4.2
- MP3 player with USB/SD interface, FM/DAB+ radio, LED display, infrared remote control
- Reception of interference-free 'digital radio' (DAB+)
- 1 balanced XLR microphone input with 48 V phantom power and priority selection for announcements
- 2 unbalanced inputs, switchable mic/line
- 2 unbalanced line inputs
- 1 TEL input
- 1 Music-On-Hold output (MOH)
- Speaker outputs via screw contacts
- Mute function via screw contact
- 2 line outputs
- Input level control and output level control
- 2-way tone control for the output
- LEDs for indicating operation, clipping, protect and signal level



TECHNICAL SPECIFICATIONS

PA-803DAP

Weight

Power rating 30 W
Channels 1
Zones 1

4.5 mV/600 Ω (channel 1),

Inputs 120 mV (channels 2-3),

60 mV (channels 4-5)

90 mV (tel.)

Frequency range 60-15,000 Hz

Equalizer bass yes
Equalizer treble yes

S/N ratio 72 dB (mic, channels 1-3)

85 dB (line, channels 2-5)

THD < 0.5%Phantom power 48 VMains voltage $\sim 230 \text{ V}$ Mains frequency 50 Hz

Power consumption, operation 100 VA

Operating voltage (possible alternative) DC 24 V

Power supply (possible alternative) 2.5 A

Admiss. ambient temp. 0-40 °C
Width 320 mm
Height 95 mm
Depth 245 mm

1 x XLR (channel 1),

3.95 kg

2 x 6.3 mm jack (channels 2-3), 2 x RCA L/R (channels 4-5),

2 x RCA (record out),

Connections 1 x F jack (FM/DAB+), screw contacts (tel. input),

screw contacts (MOH), screw contacts (DC 24 V), screw contacts (mute), screw contacts (speakers)

Packing dimensions (W x H x L) $0.39 \times 0.16 \times 0.31 \text{ m}$

Gross weight 4.33 kg
Net weight 3.74 kg



PA-803DAP - Page: 3

