



## PA-888D

Order No.: 17.6730

Price upon request

### PRODUCTINFOS

#### Mono class D PA mixing amplifier

- 1 x 60 W
- Class D concept with a high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- 2 microphone inputs, 1 aux input
- Chime, siren and fog horn (saved as MP3 files in internal memory, other files can be played via USB port), adjustable level
- Bass, treble and master controls
- 6-step LED level display
- Protective circuit with LED indication for protection
- Mains operation or 12-24 V battery operation

### TECHNICAL SPECIFICATIONS

#### PA-888D

Peak output power	80 W
Power rating	60 W
Power rating at 4 $\Omega$	60 W

**PA-888D**

Power rating at 8 $\Omega$	35 W
Power rating at 100 V	60 W
Channels	3
Inputs	3.5 mV/1 k $\Omega$ (mic), 35 mV/2 k $\Omega$ (aux)
Frequency range	100-18,000 Hz
Equalizer bass	$\pm$ 10 dB/100 Hz
Equalizer treble	$\pm$ 5 dB/10 kHz
S/N ratio	> 67 dB
THD	< 0.05%
Mains voltage	$\sim$ 230 V
Mains frequency	50 Hz
Power consumption, operation	220 VA
Operating voltage (possible alternative)	DC 12 V, DC 24 V
Power supply (possible alternative)	DC 3.9 A
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	320 mm
Height	95 mm
Depth	240 mm
Weight	4.3 kg
Connections	2 x 6.3 mm jack (mic), 1 x 6.3 mm jack (aux), 1 x micro USB, screw terminals (speakers)