













# **PA-914D**

Order No.: 1000143

## **PRODUCTINFOS**

## Mono class D PA mixing amplifier

- 1 x 140 W
- Class D concept with PASCAL amplifier module
- Energy-efficient concept due to high efficiency
- Lightweight design due to compact switch-mode power supply
- · Silent operation due to fanless cooling concept
- 4 balanced mic/line inputs
- · Mic 1 with priority circuit and automatic talkover
- Additional connection for desktop microphone via screw terminal
- 1 aux input
- Speaker outputs via screw contacts
- Line output
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- Input level control and output level control
- 2-way tone control for the output
- 48 V phantom power supply for each microphone input, to be activated individually
- Limiter switch: 8 Ω/100 V
- · Removable mounting brackets

## **TECHNICAL SPECIFICATIONS**

#### **PA-914D**

Power rating



#### **PA-914D**

Power rating at 8  $\Omega$  140 W

Power rating at 100 V  $\,$  140 W/66  $\Omega$ 

Output impedance 8  $\Omega$  Channels 5

3 mV (mic),

Inputs 200 mV (line),

140 mV (aux)

Frequency range 20-20,000 Hz

Integrated limiter yes

Equalizer bass  $\pm$  10 dB/100 Hz Equalizer treble  $\pm$  10 dB/10 kHz

S/N ratio  $> 80 \ dB$  THD < 0.1% Phantom power  $48 \ V$ 

Power supply ~ 90-230 V/50-60 Hz/160 VA

Mains voltage ~ 90-230 V

Mains frequency 50-60 Hz

Power consumption, operation 160 VA

Admiss. ambient temp. 0-40 °C

Width 482 mm

Height 88 mm

Depth 275 mm

Rack units, RU 2
Weight 5.1 kg

4 x XLR (mic/line),

Connections 1 x RCA L/R (aux),

screw contacts (speakers)

Packing dimensions (W x H x L)  $0.5 \times 0.13 \times 0.36 \text{ m}$ 

Gross weight 6.14 kg
Net weight 5.14 kg